

Mini Dry Bath

MiniHCL100/MiniHC100/MiniH100

Portable and option to power by automobile power adapter

Features

- Mini, lightweight, safe with LCD display
- Digital control over both temperature and time
- Built-in user recalibration function guarantees long term temperature accuracy
- Overheating protection
- Optional cooling function
- Interchangeable blocks for a wide variety of test tube sizes
- Mini HCL100 with hot lid to prevent water condensing on the tube cap



Applications

Useful for rapid and uniform heating of biological samples in applications like preservation, denaturation of nucleic acids and proteins, and many other applications.

Specifications	Mini HCL100	Mini HC100	Mini H100
Display	LCD	LCD	LCD
Temperature setting range[°C]	0-100	0-100	25-100
Temperature range [°C]	Room temperature-23~100	Room temperature-23~100	Room temperature+5~100
Temperature control accuracy[°C]	±0.5	±0.5	±0.5
Temperature display accuracy[°C]	0.1	0.1	0.1
Minimum time taken for heating(25°C+100°C)	≤20min	≤20min	≤20min
Minimum time for cooling(20°C-0°C)	≤25min	≤25min	-
Max. Heating Rate	8°C/min	8°C/min	6.5°C/min
Max. Cooling Rate	3°C/min	3°C/min	-
Time setting range	0-999min/0-999sec	0-999min/0-999sec	0-999min/0-999sec
Program Memory	9(2steps for each)	9(2steps for each)	9(2steps for each)
Temperature self-calibration	Support	Support	Support
USB interface	Support	Support	Support
Error code display	Support	Support	Support
Dimension[WxDxH]	110x162x140mm	110x162x140mm	110x162x140mm
Total Weight [kg]	≤1	≤1	≤1
Voltage,Frequency	100-240V, 50/60Hz or DC12V	100-240V, 50/60Hz or DC12V	100-240V, 50/60Hz or DC12V
Power [w]	60	60	60
Operating temperature[°C]	+10-40	+10-40	+10-40
Operating humidity [% RH]	≤80	≤80	≤80