



Value-Line Ductless Fume Hood



Topair's Value-line Ductless Fume Hood provides a safe work environment for lab staff working with acids and harsh chemicals.

A cost-effective benchtop ductless fume hood with an innovative, intelligent control system that includes a 7" color touchscreen with airflow monitoring and alarm and integral polypropylene worktop, a sliding front sash with counterweight, and an environmentally friendly EC fan, an LED light.

A Variety of filters can be supplied for max protection from most common chemical fumes.

TopAir's Value-line Ductless Fume Hoods can be Size Customized to the requirements of each client. And a large variety of accessories is available.

- Compact, cost-effective Benchtop model.
- Polypropylene structure with high chemical Resistance.
- Built-in sealed polypropylene worktop or choice of epoxy, stainless steel, ceramic, Trespa.
- 7" touch screen with airflow display and alarm.
- Tempered glass side windows and sliding front. Sash with counterweight.
- Eco-friendly, cost-effective 800 LUX LED lighting.
- Air velocity - 0.5 ± 0.1 m/s, 100 ± 20 FPM.
- Back access for filter replacement.
- Variety of HEPA & carbon filters.
- EC fan with speed adjustment with 10 speeds
- 250mm Thimble connection to the external ducting system.
- Optional: Metal stand, Gas and water Taps



Models

Spec/Model	VL-CF-075-PP	VL-CF-090-PP	VL-CF-120-PP
Outer Dimensions (W x D x H)	750 x 580 x 1050 mm 29.5 x 22.8 x 41.3"	900 x 580 x 1050 mm 35.4 x 22.8 x 41.3"	1200 x 580 x 1050 mm 47.2 x 22.8 x 41.3"
WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS			
Workspace (W x D x H)	730 x 450 x 550 mm 28.7 x 17.7 x 21.6 "	880 x 450 x 550 mm 34.6 x 17.7 x 21.6 "	1180 x 450 x 550 mm 46.4 x 17.7 x 21.6 "
Max Sash Working height	350 mm / 13.8"		
Equipment Entry Opening	500 mm / 19.7"		
Microprocessor control	7" full touch screen with Airflow alarm, 10-speed Fan control, filter timer, service timer, lights control		
Air Velocity	0.5±0.1 m/s, 100±20 FPM		
Hood Material	Welded white polypropylene structure, With built-in sealed PP worktop		
Noise Level (Tested 20 cm from the worktable, 1.2m above ground)	<52dB	<55dB	<57dB
Power Supply	110 / 220V, 50/60 Hz, Single phase		
Illumination	800 LUX, Eco-friendly LED lighting		
Filter	Carbon filters for solvents, acids, bases, formaldehyde, multi-gas (a blend of materials) /HEPA/ULPA		

Accessories

Spec/Model	VL-CF-075-ST	VL-CF-090-ST	VL-CF-120-ST
Stand WxDxH	750 x 520 x 800 29.5 x 20.6 x 31.5"	900 x 520 x 800 mm 35 x 20.6 x 31.5"	1200 x 520 x 800 mm 47.2" x 20.6 x 31.5"

Tel : 1-855-6-TOPAIR International: +1-855-686-7247 Email: sales@topairsystems.com
www.topairsystems.com | Headquarters: 300 First Avenue, Suite 102, Needham, MA 02494 USA