

Biochemistry Incubator



Features:

- * Polished stainless steel chamber.
- * CFC-free eco-friendly refrigerant.
- * BOD socket integrated inside for additional small equipment.
- * Round angle structure, easy to clean.
- * Microprocessor PID temperature control, accurate and reliable.
- * Universal castors for easy movement.

Safety Functions:

- * Temperature protection threshold value can be set.
- * Auto-off protection and alarm for abnormal situation.
- * Parameters can be saved automatically when power off or system error.

Optional Accessories:

- * Test port.

Technical Parameters:

Model	KOELBRO80	KOELBRO160	KOELBRO202	KOELBRO251	KOELBRO304	KOELBRO397
Capacity	80L	160L	202L	251L	304L	397L
Temp. Range	5~50°C (type II 0~65°C)					
Temp. Fluctuation	±1°C (type II & III: heating: ±0.5°C to ±1°C)					
Temp. Uniformity	±2°C					
Shelves	2 pcs/adjustable	3 pcs/adjustable				
Time Range	0~9999min					
Refrigerant	R134a (CFC free, eco-friendly)					
BOD socket	1pc					
Consumption	650W	710W	760W	810W	960W	1280W
Power Supply	AC220V±10%, 50/60Hz					
Internal Size(mm)	400*370*550	450*420*850	450*450*1000	480*490*1070	520*500*1170	580*540*1270
External Size(mm)	540*570*1070	600*670*1470	590*640*1520	620*680*1590	660*690*1690	720*740*1790
Package Size(mm)	700*730*1260	740*810*1650	750*800*1710	780*840*1780	820*850*1880	880*900*1980
Gross Weight(kg)	85	145	146	147	157	170