

Data sheet

Cooled Incubator (ST) ST 500 Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on

TECHNICAL DATA

air convection	forced
chamber capacity [l]	500
working capacity [l]	469
controller	microprocessor PID
display	4,3" full colour touch screen

TEMPERATURE

temperature range [°C]	+3...+40 / +70 (opcja)
temperature resolution every ... [°C]	0,1
temperature fluctuation at 37°C [°C]	0,3
temperature variation at 37°C [°C]	0,6
over temperature protection	class 1.0 to DIN 12880 / class 3.3 (option)

CHAMBER


door type	solid / glass or double (option) /5/
interior	
B Smart	aluminium
C Smart	stainless steel to DIN 1.4016
CS Smart	stainless steel to DIN 1.4016
P Smart	acid-proof stainless steel to DIN 1.4301
PS Smart	acid-proof stainless steel to DIN 1.4301
housing	
B Smart	powder coated sheet
C Smart	powder coated sheet
CS Smart	stainless steel polished
P Smart	powder coated sheet
PS Smart	stainless steel polished

overall dims [mm] /1/

width A	660
height B	1990
depth C	810

internal dims [mm]

width D	480
width D'	510
height E	1510
depth F	610
height I	1380



shelves (standard max)	3 11
max shelf workload [kg] /2/	20
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	100
weight [kg]	105

ELECTRICAL PARAMETERS

voltage*	230V 50-60Hz
nominal power [W]	650
refrigerant	R290 / GWP=3
warranty	24 months
manufacturer	POL-EKO-APARATURA

all the above technical data refer to standard units (without optional accessories)

* - other power supplies on request

1 - depth doesn't include 50 mm of power cable


2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

5 - additional internal glass door

OPTIONS AND ACCESSORIES




Order number: */C

Internal glass door



Order number: */A

External glass door



Order number: */P


Wire shelf



INOX


Order number: */P INOX

Stainless steel wire shelf




Order number: */PP

Perforated shelf




Order number: */PW

Reinforced shelf



Order number: KUW GN*/*


Stainless steel cuvettes



ALU

Order number: ST/CHL/SWP ALU


Aluminum drawer with powder coated slides



INOX

Order number: ST/CHL/SWP INOX













Stainless steel drawer with powder coated slides



INOX/INOX

Order number: ST/CHL/SWPN INOX

Stainless steel drawer with stainless steel slides

	Order number: QLK*	Wheels
	Order number: ST/70	Extended temperature range to 70°C
	Order number: */FOT	Photoperiodic system
	Order number: GNZ	Internal socket
	Order number: OCZ/N	Non-standard access port for external sensor
	Order number LabDesk	LabDesk - software
	Order number: BRT*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
	Order number: */3.3	Over temperature protection 3.3 class according to DIN 12880
	Order number: */RK	Chart recorder
	Order number: ZKM	Magnetic door lock
	Order number: BPP 12	Battery backup for display
	Order number: PORT ALARM	Dry alarm contact