

Data sheet

Ultra-Low Freezer ZLN-UT 200 VIP Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters - Alarm Bar
- operating with gloves on



Smart - preview screen






tel. (+48) 32 453 91 70

A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

natural
259
192
microprocessor PID
4,3" full colour touch screen
vacuum - VIP panels
-8650
0,1
160
50
1,5
4,0
solid
stainless steel to DIN 1.4016
DIN 1.4301
powder coated sheet
powder coated sheet

overall dims [mm] /1/	
A width	880
B height	1390
depth C	960
internal dims [mm]	
width D	620
height E	770
depth F	580
height I	360



shelves (standard max)	2/2
max shelf workload [kg] /2/	10
number of internal chambers	2
max unit workload [kg]	65
weight [kg]	200





A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

ELECTRICAL PARAMETERS			
power supply	230V 50-60Hz		
nominal power [W]	2100		
refrigerant	R290 / GWP=3 R170 / GWP=6		
warranty	24 months		
manufacturer	POL-EKO-APARATURA		

all the above technical data refer to standard units (without optional accessories)

K = +/- (T average max. - T average min.) / 2

OPTIONS AND ACCESSORIES

LAB DESK	Order numberLabDesk	LabDesk software
ALARM	Order number: PORT ALARM	Dry alarm contact
USB	Order number: USBK	USB cable
LAN	Order number: LANK	LAN cable



st - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

^{** -} other power supplies on request

^{1 -} depth doesn't include 50 mm of power cable