

3035UE



2- door tall safety cabinet Type 30

COMPLIANCE

EN 14470-1, FM 6050

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Pedestal area under-driveable by a forklift by removing panel
- Tested and approved according to FM 6050



TECHNICAL FEATURES

Model	3035UE	Shipping dimensions HxWxD (mm)	1950 x 1200 x 800
Compliance	EN 14470-1, FM 6050	Ventilation	Both inlet and outlet on the back wall of the cabinet
Cabinet materials	Melamine wood structure	Openings diameter (mm)	100
Doors color	light grey RAL 7035	Number of compartments	1
Number of doors	2	Containment sump	1
Doors type	swing doors		210.00
Hinges	right & left	HS Code	94036000
Door closure	self-closing		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump for cabinets 3033UE - 3035UE (Réf : B35U)
- Retention shelf for cabinets 3033UE - 3035UE (Réf : E35U)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3035UE	1731 x 1092 x 457	1330 x 978 x 325	170		2	50	210.00