

## 2- door tall safety cabinet Type 30

### COMPLIANCE

EN 14470-1, FM 6050

### ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

### BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Pedestal area under-driveable by a forklift by removing panel
- Tested and approved according to FM 6050



### TECHNICAL FEATURES

Model	<b>3033UE</b>	Shipping dimensions HxWxD (mm)	<b>2180 x 1200 x 800</b>
Compliance	<b>EN 14470-1, FM 6050</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Cabinet materials	<b>Melamine wood structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>light grey RAL 7035</b>	Number of compartments	<b>1</b>
Number of doors	<b>2</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>		<b>170.00</b>
Hinges	<b>right &amp; left</b>	HS Code	<b>94036000</b>
Door closure	<b>self-closing</b>		

### ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

### OPTIONS

- Containment sump for cabinets 3033UE - 3035UE (Réf : B35U)
- Retention shelf for cabinets 3033UE - 3035UE (Réf : E35U)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3033UE	1198 x 1092 x 537	795 x 980 x 325	113		1	50	170.00