

# Compact Shaker KS 15 B control



## Description

The programmable Horizontal Shaker KS 15 B control with touch display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

### Basic Equipment

Basic device without rack system.

With touch display and programmable control

### Loading Capacity

Erlenmeyer flasks 100 ml 20 pieces

Erlenmeyer flasks 250 ml 12 pieces

Erlenmeyer flasks 500 ml 6 pieces  
Erlenmeyer flasks 1000 ml 4 pieces  
Separating funnels 250 ml 1 pieces

You will find further loading possibilities [here](#)

### Options

[USB 2.0 interface](#)

[RS 232 interface](#)

[Control interface](#)

[Safety Package](#)

## Details

**Motion:** reciprocating (horizontal)  
**Shaking platform:** 400 x 300 mm  
**Max. load:** 15 kg  
**Shaking speed:** 30 - 420 rpm, in steps of 5  
**Stroke:** 17 mm  
**Runtime:** programmable / continuous  
**Order No.:** 6172 000  
**Accessory:** Rack System Combifix KS  
Universal tray KS  
Incubator Hood TH 15

## Technical specifications

**Electrical supply:** 230 V or 115 V, 50 / 60 H please indicate in case of order  
**Enclosure protection:** IP 21  
**Heat emission:** approx. 7 W  
**Relative humidity:** ~ 85 %  
**Dimensions (w x d x h):** 510 x 490 x 150 mm  
**Weight:** 19 kg  
**Ambient temperature:** 5°C bis 50°C