

## Large Capacity Vertical Type Shaking Incubator (Double Door & Double Layer)



### Features:

- \* Audio and visual alarm.
- \* Power off recovery function.
- \* Soft shaking mode, stable and reliable operation.
- \* Efficient drive motor and cooling controller, low energy consumption.
- \* Transparent window and built-in lighting design convenient for observation samples.
- \* Accessories: UV lamp(standard accessory); Humidity controller, Inlet air pipe, Light system(optional accessories).

### Technical Parameters:

Model	SCHINCUVG11	SCHINCUVG21
Controller	PID	
Display	LCD	
Circulation Mode	Forced convection	
Shaking Mode	Rotary shaking	
Drive Mode	Unishaft drive	
Rotating Speed	30~300rpm	
Rotating Accuracy	±1rpm	
Vibration Range	Φ25mm	
Temp. Range	RT+5~60°C	4~60°C
Temp. Control Accuracy	±0.1°C	
Temp. Uniformity	±1°C	
Timing Range	0~999.59h	
Shaking Plate Size	734*464 mm	
Shaking Plate Quantity	2 pcs	
Max. Capacity	1000ml*24 or 500ml*44 or 250ml*56 or 50ml*104	
Standard Capacity	500ml*22, 250ml*28	
Internal Material	Stainless steel	
External Material	Cold-rolled steel with anti-bacteria powder coating	
Refrigerant	/	CFC-Free, 134A
Cooling Consumption	/	200W
Heating Consumption	500W	
Safety Function	Audio and visual alarm for over-temperature; Alarm for over-speed; Independent over-temperature protector; Shutdown protection for door opening; Leakage or over-current protection.	
Consumption	930W	1200W
Power Supply	AC110/220V±10%, 50/60Hz	
Internal Size(W*D*H) mm	850*520*760	
External Size(W*D*H) mm	950*740*1400	
Package Size(W*D*H) mm	1050*840*1550	
Gross Weight(kg)	395	