

## Stacked Large Capacity Shaking Incubator



### Features:

- \* Audio and visual alarm function.
- \* Advanced unishaft drive, low noise.
- \* Eight self-compiled programs, with different speed and time setting.
- \* Shaking plate is made of electroplating aluminum, anti-rust or anti-corrosion.
- \* Automatic operation, auto-stop, timing, time display, parameters memory and recovery function.
- \* Automatic power-off protection system when the motor is overheating and temperature is out of control.
- \* Accessories: UV lamp(standard accessory); Humidity controller, Inlet air pipe, Light system(optional accessories).

### Technical Parameters:

Model	SCHINCUS12	SCHINCUS12R
Controller	PID	
Display	LCD	
Circulation Mode	Forced convection	
Shaking Mode	Rotatory shaking	
Drive Mode	Unishaft drive	
Temp. Range	RT+5~60°C	4~60°C
Temp. Accuracy	±0.1°C	
Temp. Uniformity	±1°C	
Rotating Speed	30~300rpm	
Rotating Accuracy	±1rpm	
Vibration Range	Φ25mm	
Refrigerant	/	CFC-Free, 134A
Cooling Consumption	/	200W
Heating Consumption	800W	
Timing Range	0-999.59h	
Shaking Plate Size	780*480mm	
Standard Capacity	250ml*40	
Max. Capacity	2000ml*12 or 1000ml*15 or 500ml*28 or 250ml*40	
Internal Material	Mirror stainless steel	
External Material	Cold-rolled steel with anti-bacteria powder coating	
Safety Function	Audio and visual alarm for over-temperature; Alarm for over-speed; Independent over-temperature protector; Shutdown protection for door opening; Leakage or over-current protection.	
Consumption	960W	1120W
Power Supply	AC110/220V±10%, 50/60Hz	
Internal Size (W*D*H) mm	870*550*395 (per unit)	
External Size (W*D*H) mm	1150*780*640(per unit)	
Package Size (W*D*H) mm	1200*830*740mm(per unit)	
Gross Weight(kg)	190 (per unit)	